

**TYPICAL SECTION – 60' RIGHT OF WAY
(LOCAL NON-RESIDENTIAL STREET)**


NOT TO SCALE

NOTES:

THE JOINT BETWEEN THE CURB AND PAVEMENT MUST BE SEALED WITH A HOT AC MATERIAL.

FOR ARTERIAL AND COLLECTOR STREETS, SEE THE PLANNING AND ZONING CODE CHAPTER 1166 DESIGN STANDARDS FOR MINIMUM PAVEMENT STANDARDS.

- ① ODOT ITEM 448 – 1" ASPHALT CONCRETE SURFACE COURSE, TYPE 1, PG 64-22
- ② ODOT ITEM 448 – 1 1/2" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE 1, PG 64-22
- ③ ODOT ITEM 301 – 6" ASPHALT CONCRETE BASE COURSE
- ④ ODOT ITEM 304 – 4" AGGREGATE BASE (CRUSHED LIMESTONE)
- ⑤ ODOT ITEM 203 – SUBGRADE COMPACTION
- ⑥ ODOT ITEM 609 – COMBINATION CURB AND GUTTER, TYPE 2 WITH 6" ODOT 304 AGGREGATE BASE (CRUSHED LIMESTONE)
- ⑦ ODOT ITEM 407 – TACK COAT (0.10 GAL/SY)
- ⑧ ODOT ITEM 408 – BITUMINOUS PRIME COAT (0.40 GAL/SY)
- ⑨ ODOT ITEM 659 – SEEDING AND MULCHING INCLUDING 2" TOPSOIL
- ⑩ ODOT ITEM 608 – 5" CONCRETE SIDEWALK
- ⑪ ODOT ITEM 304 – 4" AGGREGATE BASE
- ⑫ ODOT ITEM 605 – 4" UNDERDRAIN (ODOT 707.31) WITH GEOTEXTILE WRAP (SOCK) AND NO. 8 GRAVEL BEDDING TO TOP OF PIPE AND ODOT ITEM 304 BACKFILL TO 4" BELOW TOP OF CURB



**CITY OF ALLIANCE
ENGINEERING DEPARTMENT**
504 E. MAIN ST.
ALLIANCE, OH 44601
PHONE: (330) 823-5122 FAX: (330) 829-2236

TYPICAL SECTION ASPHALT ROADWAY DETAIL
60' R/W
NOT TO SCALE

ENGSERV1 / E:/ DATA / ENGINEERING DOCUMENTS / STANDARD DRAWINGS/ COASTANDARDS.DWG

APPROVED BY:

VINCENT MUESER, P.E., S.I.T.
ALLIANCE CITY ENGINEER

**ALLIANCE RD-2
(1 OF 1)**

Revisions / Drawn By

02-19-10 / CAF